

# WET/WET HIGH ACCURACY PRESSURE CALIBRATORS WITH BUILT-IN RS-232 COMMUNICATIONS

## DISCONTINUED

PCL31  
**\$1095**

**Compact,  
Easy-to-Use!**

PCL33, \$1795, dual range model, shown smaller than actual size.

**Electrical  
Test Leads  
Included!**



- ✓ NIST Traceable Certificate Included
- ✓ Compatible with Most Liquids
- ✓ Small Size
- ✓ High Accuracy 0.05% of Reading
- ✓ No Temperature Effect from 0 to 50°C (32 to 122°F)
- ✓ Eight Unit Scales to Choose from
- ✓ 9 V Battery Powered Included (60 hr typ)

### SPECIFICATIONS

#### Pressure

**Accuracy (1 year):** Includes all effects of linearity, hysteresis, repeatability and temperature

#### Port 1:

±[0.05% rdg + 0.005% FS (36 psi)]

Vacuum: ±[0.25% rdg + 0.025% FS (-14.7 psi)]

#### Scale Resolution

inH <sub>2</sub> O	0.01
psi	0.001
kPa	0.01
mmH <sub>2</sub> O	1
mmHg	0.01
inHg	0.001
kg/cm <sup>2</sup>	0.0001
mbar	0.1

#### Port 2:

±[0.05% rdg + 0.005% FS (3000 psi)]

#### Scale Resolution

psi	0.1
Bar	0.01
kPa	1

#### Agency Approvals (Pending):

Factory Mutual Intrinsically Safe IS/II/1/ABCD, IS/II/1/EG



- ✓ High Contrast LCD Display
- ✓ Low Pressure: Scroll and Select From 7 Scales
- ✓ High Pressure: Scroll and Select From 3 Scales
- ✓ RS232 Port
- ✓ Zero/Tare: Both Ranges
- ✓ mA/%: Scroll Between: Direct mA readings 0 to 100% of 4 to 20 mA 0 to 100% of 10 to 50 mA

#### Physical

##### Media Compatibility:

Liquids and gasses compatible with PFA penetrated-hard anodized aluminum, 316 stainless steel and FKM

##### Power:

9 V alkaline included (low bat indication) standard 60 hr typical life without RS-232 40 hr typical life using RS-232

##### Pressure Connection:

1/8 NPTF RS232 Connection: 9-position PC card I/O receptacle; mating connector P/N 621370-1

##### Dimensions:

130 H x 70 W x 29 mm D (5.1 H x 2.8 W x 1.1" D)  
Case: Extruded aluminum  
Weight: 385 g (13.5 oz)

#### Electrical

**Range:** 0 to 55 mA

**Resolution:** 0.001 mA

**Accuracy:** ±(0.025% rdg + 0.001 mA)

#### Percent Conversion:

4 mA = 0.00%, 20 mA = 100.00%  
10 mA = 0.00%, 50 mA = 100.00%

#### Temperature

**Operating:** 0 to 50°C (32 to 122°F)  
**Compensated:** 0 to 50°C (32 to 122°F)

**Storage:** -20 to 70°C (-4 to 158°F)

**RS232 Comm:** All models



**MOST POPULAR MODELS HIGHLIGHTED!**

### To Order (Specify Model Number)

MODEL NO.	PRICE	INPUT RANGES	MAX PRESSURE
PCL31	\$1095	Vacuum to 36 psi	100 psi
PCL31H	1195	0 to 3000 psi	4500 psi
PCL33	1795	Port 1: Vacuum to 36 psi Port 2: 0 to 3,000 psi	100 psi 4,500 psi

Comes with NIST traceable calibration certificate, 9 V alkaline battery, soft carrying case, test leads and complete operator's manual.

**Ordering Example:** PCL33 is a dual range (vacuum to 36 psi and 0 to 3,000 psi) calibrator, \$1795.

# DISCONTINUED

# omega.co.uk<sup>®</sup>

Your One-Stop Source for Process Measurement and Control!

Freephone 0800 488 488 | International +44(0) 161 777 6622 | Fax +44(0) 161 777 6622 | Sales@omega.co.uk

[www.omega.co.uk](http://www.omega.co.uk)



#### UNITED STATES

[www.omega.com](http://www.omega.com)

1-800-TC-OMEGA  
Stamford, CT.

#### CANADA

[www.omega.ca](http://www.omega.ca)

Laval(Quebec)  
1-800-TC-OMEGA

#### GERMANY

[www.omega.de](http://www.omega.de)

Deckenfronn, Germany  
0800-8266342

#### UNITED KINGDOM

[www.omega.co.uk](http://www.omega.co.uk)

Manchester, England  
0800-488-488  
+44-(0)161-777-6611

#### FRANCE

[www.omega.fr](http://www.omega.fr)

0800-466-342

#### BENELUX

[www.omega.nl](http://www.omega.nl)

0800-099-33-44



## More than 100,000 Products Available!

### • Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders, Relative Humidity Measurement Instruments, PT100 Probes, PT100 Elements, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples, Thermowells and Head and Well Assemblies, Transmitters, Thermocouple Wire, RTD Probes

### • Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

### • pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

### • Data Acquisition

Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485, Ethernet and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

### • Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Pressure Transmitters, Strain Gauges, Torque Transducers, Valves

### • Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters